

# Adapters and terminators

	Artikel	Beschreibung	Bestell-Nr.
	PG 11M - IEC 14f	Adapter PG 11-male to IEC-female with M 14 thread	60280100
	PG 11M - 3,5/12f	Adapter PG 11-male to 3,5/12-female	60280301
	Fm - 3,5/12f	Adapter F-male to 3,5/12-female	60280406
	PG 11M - Ff	Adapter PG 11-male to F-female	60280600
	90 - Fm - Ff HQ	Angled adapter F-male to F-female	60280811
	IEC 14f - IEC 14f	Adapter IEC-female to IEC-female	60280900
	IEC 14f - Ff	Adapter IEC-female to F-female	60280905
	IEC 14f - CHASSIS Ff	Adapter IEC-female to F-female as chassis connector	60280910
	3,5/12M - IEC 14f	Adapter 3,5/12-male to IEC-female with M 14 thread	60281005
	3,5/12M - Ff	Adapter 3,5/12-male to F-female	60281010
	3,5/12M - 3,5/12M	Adapter 3,5/12-male to 3,5/12-male	60281011
	3,5/12f - 3,5/12f CHASSIS	Adapter 3,5/12-female to 3,5/12-female as chassis connector with PG 11 thread	60281000
	3,5/12f CHASSIS - Ff	Adapter 3,5/12-female to 3,5/12-female as chassis connector with PG 11 thread	60281020
	BNCf 75 Ohm - Fm	Adapter BNC-female to F-female 75 Ohm	60281710
	BNCf 75 Ohm - IECf	Adapter BNC-female to IEC-female	60281750
	5/8M - IEC 14f	Adapter 5/8-male to IEC-female with M 14 thread	60280210
	5/8M - Ff	Adapter 5/8-male to F-female	60280500
	5/8M - 3,5/12f	Adapter 5/8-male to 3,5/12-female	60280550
	5/8 - PG 11	Adapter ring 5/8-male to 3,5/12-female	60280565
	PG 11M-R 75 AC Blocking	PG 11-male as 75 Ω terminator with AC blocking	60260100
	IEC 14M-R 75 AC Blocking	IEC-male with M 14 cap nut as 75 Ω terminator with AC blocking	60260200
	3,5/12M-R 75 AC Blocking	3,5/12-male as 75 Ω terminator with AC blocking	60260300
	5/8m-R 75 AC Blocking	5/8-male as 75 Ω terminator with AC blocking	60260500



KLASSE  
A  
CLASS

KLASSE  
A  
CLASS

KLASSE  
A  
CLASS

KLASSE  
A  
CLASS

Artikel	Beschreibung	Bestell-Nr.
PG 11M - AC	PG 11-male as power feed-in for remote power	60290401
5/8M - AC	5/8-male as power feed-in for remote power	60290501
3,5/12M - AC	3,5/12-male as power feed-in for remote power	60290601
Double splice FM-FM	Double splice – F-male to F-male adapter, 27 mm length, nickel plated brass	54210000
F-plug-in adapter Ff-Fm/P	F-plug-in adapter for measures, fits on every F-female without screwing	54220000
F-Schnellstecker Ff-Fm/P HQ	F-plug-in adapter HQ for measures, fits on every F-female without screwing	54220100
F-Adapter FM-IECMP	F-adapter – F-male to IEC-male	56020000
F-Adapter FF-IECMP	F-adapter – F-female to IEC-male	56030000
F-Adapter FF-IECMP HQ	F-adapter HQ – F-female to IEC-male	56030500
F-Adapter FM-IECFP	F-adapter – F-male to IEC-female	56070000
F-Adapter FF-IECFP	F-adapter – F-female to IEC-female	56080000
F-Adapter FF-BNCM	F-adapter – F-female to BNC-male	56040000
F-Adapter FF-BNCM HQ	F-adapter HQ – F-female to BNC-male	56040001
TR-59-1/4-HQ	F-terminal resistor 75 Ω – nickel plated brass	54420000
CC-LT-R-75-ST with F-thread, long	Tamper-proof terminal resistor – 75 Ω F-terminator for unused outputs, to avoid signal-theft or interference ingress, only to open with LTT-75 (please find further information within our tools catalogue), with F-thread (26 mm)	54431000
CC-LT-R-75-S without F-thread, short	Tamper-proof terminal resistor – 75 Ω F-terminator for not used outputs, to avoid signal-theft or interference ingress, only to open with LTT-75 (please find further information within our tools catalogue), without F-thread (20 mm)	54432000
CC-Security Shield	In order to secure F-connections against manipulation and unauthorized disassembly, diameter 20 mm, only mountable/removable with speciality tool (Order No. 55445000), please find further information within our tools catalogue	54440000
180-FF-FF-HQ/180-FF-FF-HQ	F-female to F-female adapter with NITIN surface in U-style, gold-plated pins, through loss < 0,2 dB, return loss > 30 dB, screening > 100 dB, transfer impedance < 0,3 mΩ/connector	54510000
F-81-HQ-1 F-splice prof.	F-female to F-female adapter, nickel plated brass, 26 mm length, screening > 96 dB, return loss > 30 dB	54500000
F-NUT + WAL	F-nut and wal for F-81-HQ	54391000
Double splice female	F-female to F-female adapter with high return loss	54200000
F-angle adapter	F-male to F-female adapter with soldered inner pin, nickel plated brass	54190000