

CX3 Quick Mount™ connectors

54263909
F-CX3 4,0 QM
SHORT

54263915
F-CX3 4,5 QM
SHORT

54263916
F-CX3 5,0 QM
SHORT

54263917
F-59-CX3 6,0 QM

54265105
F-56-CX3 7,0 QM

54266002
FM-RG11-CX3 QM 10,5

54269304
3,5/12m-RG11-CX3
QM 10,5



Universal waterproof compression connectors with NITIN coating, type selection is only based on the outer diameter of the coaxial cable, therefore suitable for a variety of different coaxial cables.

Very simple installation: Only the cable sheath and the inner conductor have to be stripped (each 6,5 mm), the connector is then simply plugged on the cable. There is no need to fold back the braid anymore!

Return loss > 30 dB
Screening > 120 dB
Transfer impedance < 0,1 mΩ/connector



Item	Order No.
F-CX3 4,0 QM SHORT Coax cables with outer diameter of 3,6 – 4,4 mm, outer conductor 2,8 – 3,5 mm, mounting only with compression tool (Order No. 55415500), please find further information concerning compression tools within our tools catalogue	54263909
F-CX3 4,5 QM SHORT Coax cables with outer diameter of 4,3 – 4,9 mm, outer conductor 3,0 – 3,7 mm, mounting only with compression tool (Order No. 55415500), please find further information concerning compression tools within our tools catalogue	54263915
F-CX3 5,0 QM SHORT Coax cables with outer diameter of 4,9 – 5,4 mm, outer conductor 3,6 – 4,4 mm, mounting only with compression tool (Order No. 55415500), please find further information concerning compression tools within our tools catalogue	54263916
F-59-CX3 6,0 QM Coax cables with outer diameter of 5,0 – 6,7 mm, outer conductor 3,8 – 4,5 mm, mounting only with compression tool (Order No. 55415500), please find further information concerning compression tools within our tools catalogue	54263917
F-56-CX3 7,0 QM Coax cables with outer diameter of 6,4 – 7,5 mm, outer conductor 4,7 – 5,7 mm, mounting only with compression tool (Order No. 55415300, 55415500, 55415600 or 55410100), please find further information concerning compression tools within our tools catalogue	54265105
FM-RG11-CX3 QM 10,5 Compression F-connector QUICK-MOUNT, waterproof, suitable for a wide range of cables with an outer diameter of approx. 10,5 mm, e.g. Ören HD-163	54266002
3,5/12m-RG11-CX3 QM 10,5 Suitable for a wide range of cables with an outer diameter of approx. 10,5 mm, e.g. Ören HD-163, mounting with compression tool (Order No. 55415700), please find further information concerning compression tools within our tools catalogue	54269304