



Description: Compression Connector, EX11 with movable PIN, nut 7/16".
(Measured with BETACAVI – RG11 BB3 PE Cable)

DATA SHEET

Electrical

	Specification			Standard
Frequency Range	5 MHz – 3.000 MHz			
Impedance	75 Ω nominal			
	Better Than	Measured – Worst case of 5 measurements		
Return Loss	28 dB	≥ 31.1 dB	5 MHz – 500 MHz	IEC 61169-1
	28 dB	≥ 32.4 dB	500 MHz – 860 MHz	
	28 dB	≥ 33.3 dB	860 MHz – 1.000 MHz	
	28 dB	≥ 32.2 dB	1.000 MHz – 1.750 MHz	
	28 dB	≥ 31.2 dB	1.750 MHz – 2.150 MHz	
	27 dB	≥ 30.9 dB	2.150 MHz – 3.000 MHz	
Insertion Loss of Assembly	0.08 dB	≤ 0.05 dB	5 MHz – 500 MHz	
	0.10 dB	≤ 0.07 dB	500 MHz – 860 MHz	
	0.11 dB	≤ 0.08 dB	860 MHz – 1.000 MHz	
	0.14 dB	≤ 0.11 dB	1.000 MHz – 1.750 MHz	
	0.15 dB	≤ 0.13 dB	1.750 MHz – 2.150 MHz	
	0.33 dB	≤ 0.30 dB	2.150 MHz – 3.000 MHz	
Shielding Effectiveness of Assembly (Measured with CoMeT)	Transfer Impedance @ 5 – 30 MHz ≤ 2.0 mΩ/item			IEC 62153-4-3
	Screening Attenuation @ 30 – 1.000 MHz ≥ 111.4 dB			IEC 62153-4-4
	Screening Attenuation @ 1.000 – 2.000 MHz ≥ 113.2 dB			IEC 62153-4-4
	Screening Attenuation @ 2.000 – 3.000 MHz ≥ 111.9 dB			IEC 62153-4-4
	Class: A+			EN 50117
Common Path Distortion	≤ -110 dBc			ANSI/SCTE 109 2005
Inner Conductor Resistance	≤ 3 mΩ @ 1 A DC.			IEC 61169-1
Amp. Rating	≤ 4 A @ 60 V.			
Dielectric Strength	≥ 2 KV.			IEC 61169-1
Insulation Resistance	≥ 29.99 MΩ @ 500 V.			IEC 61169-1

Environmental

	Specification	Standard
Temperature range Operating	-40°C to +85°C	
Temperature range Installation	-5°C to +50°C	
Sealing Test	IPX8 – 1 meter / 24 hours	IEC 60529
Corrosion Protection		ASTM B 117-94

Mechanical

	Specification	Standard
Interface	F male	IEC 61169-24
Cable Retention	≥ 55 kgf	ANSI/SCTE 99
Approved Compression Tool	VT-200, VT-300, CT2-AS & CT2-AS-EX	

Material and Finish

	Specification	Standard
Housing	NiSn (NITIN) plated Brass	ASTM B605
Inner conductor	NiSn (NITIN) plated Brass	ASTM B605
O'rings	EPDM	
Insulator	Polyethylene	

In order to continue to supply the best products, PPC reserves the right to change the products and specifications at any time without prior notice.

Measurement setup:

Nm-Ff - **EX11N716MPNT** – Cable – **EX11N716MPNT** – Nm-Ff.

All measurements are done with connectors mounted on BETACAVI – RG11 BB3 PE cable, length 0.5 meter.

All results are the worst case result of measurement of 5 assemblies.

All tests are performed using instruments calibrated in accordance to our ISO 9001 certification.

Return Loss, Insertion Loss and Shielding are measured with Rohde & Schwarz ZNB8 Network Analyzer, according to IEC standards.

CPD (Common Path Distortion) are measured with hp Spectrum Analyzer hp 8591E, according to SCTE standard.

In case of over current (≥ 4 A.) there is a risk for high temperature inside the connector, which can cause damage of the insulator, and / or the cable.

Further test reports, technical specifications and installation instructions can be obtained on request.

