

WAVEPACE® Pigtails OP-LC/APC

Singlemode pigtails with LC/APC connector and G.657.A1 fiber



10448903
OP-LC/APC-bl, 10 pcs



Parameter	OP-LC/APC			
Application	Single-fiber, singlemode pigtail with LC/APC connector and DIN color code to be used in connection and termination components, in- and outdoor			
Fiber type	G.657.A1			
Fiber construction	Ø 9 / 125 / 250 µm; fiber dyed through			
Core construction	LSZH loose tube fiber Ø 900 µm; (Maxi Strip)			
Color code	DIN (IEC 60304), available in 12 colors			
Length	2,0 m			
Connector quality	Classified acc. to IEC 61753 Grade B; IL: typ. ≤ 0,12 dB, max. ≤ 0,25 dB; RL: typ. > 65 dB, min ≥ 60 dB (using appropriate LC/APC adapters)			
Compatibility	Plug-compatible with LC/APC adapters IEC 61753; to be used with approved crimp, heat shrink, mini HS and mechanical splice protection elements			
Tension strength	Min. 5 N acc. to IEC 61300-2-4			
Temperature range storage & transport	-40°C – +70°C			
Temperature range operation	-25°C – +70°C			
Packaging unit	10 pcs			
Order No.	Red: 10448901 White: 10448905 Turquoise: 10448909	Green: 10448902 Gray: 10448906 Black: 10448910	Blue: 10448903 Brown: 10448907 Orange: 10448911	Yellow: 10448904 Violet: 10448908 Pink: 10448912