

House infeeds


Home entries for FTTH connections



42465609
MD1-FTTH-1x4-12



42465608
FTTH-entry-90-1x4-8mm, open



42465608
FTTH-entry-90-1x4-8mm, closed

FTTH single wall feedthrough

- Gas and watertight house entry for speedpipes and cables up to 2 bar
- Quick and easy installation without special tools
- No complex core drilling necessary
- Also suitable for angled feedthroughs
- For all common types of masonry with waterproofing according to DIN 18533 - Water penetration class W1-E and W2-E

Parameter	MD1-FttH-1x4-12	MD1-FttH-1x4-20
Diameter speedpipe/cable [mm]	4 – 12	14 – 20
Diameter drilling [mm]	16 – 20	32 – 40
Dimensions closure cap / inner diabeler / height [mm]	106 / 72 / 24	
Start of expansion [seconds]	20	
End of expansion [minutes]	2	
Curing time [minutes]	5	
Pressure load capacity [N/cm ²]	> 60	
Density [kg/m ³]	> 50	
Gas tight [bar]	≥ 2	
Pull-out resistance tube/cable [N]	> 400	
Order No.	42465609	42465610

90° FTTH infeeds

- Above-ground house entry as a visual cover for the tube entry into the building
- Integrated bending radius for safe deflection of speedpipes and cables
- Genügend Raum, um bspw. Gasblocker unterzubringen
- Sealing compound type MD+ included in the scope of delivery
- Material PC/ASA, flame retardant
- UV and weather resistant, suitable for outdoor use

Parameter	FTTH-entry-90-1x4-8mm	FTTH-entry-90-1x10-12/2x7mm
Diameter speedpipe/cable [mm]	4 – 8	10 – 12
Diameter drilling [mm]	10 – 25	22 – 32
Dimensions L x W x H [mm]	120 x 45 x 28	160 x 40 x 40
Density of the sealing compound [g/cm ³]	1,2	
Pull-out resistance tube/cable, sealing compound [N]	≥ 1,000	
Hardening of the sealant [mm/24 hours]	3	
Scope of delivery	25 infeeds & 1 cartridge sealing compound 310 ml	6 infeeds & 1 cartridge sealing compound 310 ml
Order No.	42465608	42465611

Matching accessory: 90° speedpipe branching aids

- For guided branching of speedpipes at an angle of 90°
- Can be optionally equipped with a marking ball to facilitate later location of the branch
- Material: Acrylnitrile-Butadien-Styrol ABS

Item	Form	Bending radius [mm]	Dimensions L x W x H [mm]	Packing quantity [pcs]	Order No.
LBS	L form	175	282 x 282 x 30	12	42602330
TBS	T form	175	495 x 300 x 30	12	42602423