

Professional CX3 compression F-connectors for drop and distribution cables

54263901
F-59-CX3 3,9 HEC



54264900
F-56-CX3 4,9



54265100
F-56-CX3 5,1



54266000
FM-RG11-
CX3 7,5



- All connectors are waterproof (IPX8, 1 meter/24 hours)
- Designed for very high strain relief
- Optimal fitting to the corresponding cable type
- High unalloyed brass as base material, NITIN-6 surface



Parameter	F-59-CX3 3,9 HEC	F-56-CX3 4,9	F-56-CX3 5,1	FM-RG11-CX3 7,5
For cable type	F 59 TSV and RG 59-Headend Cable	Ören HD-103 and Belden H126T00	Ören HD-113 and BKS 2050/30	Ören HD-163 and Belden PRG 11 DB + PRG 11 Cu
Length [mm]	29,0	29,0	29,0	44,0
Connector F-nut	HEX 11	HEX 11	HEX 11	HEX 14
Frequency range [MHz]	0,3 – 3.000			
Screening factor [dB]	> 100 (30 – 1.000 MHz)			
Transfer impedance [mΩ]	< 2,0/connector (5 – 30 MHz)			
Impedance [Ω]	75			
Operating temperature range [°C]	-40 ... +100			
Return loss [dB]	> 30			
Order No.	54263901	54264900	54265100	54266000