

Professional CX3 compression IEC-connectors for drop cables

54269000
IECF-56-CX3 4,9



54269200
IECF-56-CX3 5,1



54268000
IECM-56-CX3 4,9



54268200
IECM-56-CX3 5,1



54269900
O-ring and M14
nut for IEC-male



- IEC-male is waterproof in combination with O-ring and M14 nut
- Designed for very high strain relief
- Optimal fitting to the corresponding cable type
- High unalloyed brass as base material, NITIN-6 surface



Parameter	IEC-Female IECF-56-CX3 4,9	IEC-Female IECF-56-CX3 5,1	IEC-Male IECM-56-CX3 4,9	IEC-Male IECM-56-CX3 5,1	O-ring and M14 nut for IEC-male
For cable type	Ören HD-103 and Belden H126T00	Ören HD-113 and BKS 2050/30	Ören HD-103 and Belden H126T00	Ören HD-113 and BKS 2050/30	-
Length [mm]	33,5	33,5	33,5	33,5	-
Frequency range [MHz]	0,3 – 3.000				-
Screening factor [dB]	> 90 (30 – 1.000 MHz)				-
Transfer impedance [mΩ]	< 0,2/connector (5 – 30 MHz)				-
Impedance [Ω]	75				-
Ampere rating [A]	max. 6 (IEC-male) or 3 (IEC-female)				-
Operating temperature range [°C]	-40 ... +70				-
Return loss [dB]	> 20 (0,3 ... 1.000 MHz)				-
Order No.	54269000	54269200	54268000	54268200	54269900